

GEROtool® Pipe bearing frame

Safe temporary storage and professional opening or tying of PE-HD pipe pallets

The tool



In action



Special features

This pipe bearing frame enables the safe interim storage and safe opening or rebinding of pipe pallets on construction sites. The pipe bearing frame was specially developed for use with PE-HD plastic pipes. The lateral supports prevent the pipes from rolling away. This ensures the greatest possible safety at work. If required, the pipes can be re-tied directly from the frame and palletised for safe transport.

Functionality / Operation

- GEROtool® pipe bearing frame for the temporary storage of open PE-HD pipe bundles
- Set the width between the supports to the pallet width
- Insert the pipe pallet between the supports
- Loosen the Strapex straps and remove the upper timbers of the packing frames
- Remove the PE-HD pipes individually starting from the top and pass them into the application

Design and form of delivery

- GEROtool® PE-HD pipe bearing frame (63 kg) for the safe temporary storage of open pipe pallets
- Fixed and movable sides enable use with different pipe dimensions and pallet widths of up to 1.5 m
- Groove width for pallet timbers up to a maximum width of 80 mm
- Height 1.2 m and width 1.8 m

General Notes

- Several pallets can be stored on top of each other; the top edge must not exceed the height of the uprights.
- The PE-HD pipe bearing frame can be used around the wooden frames and in the free length.
- Several supports must be used to secure the pipes along the entire length. (at least 4 pipe bearing frames for a pipe length of 12 metres)
- The underground must be level, solid and free of stones or sharp-edged objects. The secure footing of the pipe bearing frame must be ensured.

Product range

Product-Nr.	Description
39333	GEROtool® PE-HD pipe bearing frame, two-part with fixed and movable side, galvanised, 1 piece